

LDH55-HAO200

55" Wall-mounted Full Outdoor Digital Signage



Features:

- · Industrial design, IP55 waterproof metal housing, tempered protective glass.
- \cdot 2500nits high brightness and anti-reflection glass is ensured excellent visibility under direct sunlight.
- \cdot Built-in temperature regulator, works well in extreme cold or hot weather.
- \cdot 178°H/178°V extra-wide viewing angle for overall viewing performance
- · Supports picture, audio, video, text display and screen control remotely.













Technical Specification

Specification

Model	LDH55-HAO200
Panel Size	55" TFT LCD
Display Ratio	9:16
Maximum Resolution	1080×1920
Display Color	16.7M
Brightness (nits)	2500cd/m²
Contrast	4000:1
Viewing Angle	178°/178°
Response Time	8ms
Backlight	LED
Network Mode	Wired, Wi-Fi, 3G/4G(optional)
Internal Speaker	5W×2

Performance

System	Android4.4
RAM	1GB
Internal Storage	8GB
Decoding Ablity	1CH@4K or 4CH@1080P

Interface

RJ45	1
USB 2.0	2
SD Card Slot	1
RS232	1

Others

Dimension	1755×850×160mm(69.1"×33.5"×6.3")
Package Size	1905×1050×310mm(wooden case)
Weight	120kg(net), 165kg(gross)
Installation Mode	Wall-mounted
Display Mode	Portrait
Protection Level	IP55(IP65 optional)
Power	AC100~240V, 50Hz/60Hz
Standard Consumption	450W(without heater), 850W(with heater)
Standby Consumption	≤2W
Work Environment	Temperature: -40 C~+50 C
	Humidity: 5%~95%