


Bastion WF5K

PN: ESWMF51H5110BCV01B
EAN: 6422956013356

Specifications

Nominal Voltage	51.2V
Rated Capacity	100Ah
Cell Technology	LifePO4
Energy Stored	5.12KWh
Battery Impedance	≤ 50 mΩ
Charging Cut-off Voltage	56.00 V
Discharge Cut-off Voltage	45.6 V
Max Charge Current	110A (environment 0° ~ 50°C)
Max Continue Discharge Current	110A (environment -10° ~ 55°C)
BMS	Included
Operating Temperature Range	-20 ~ 60°C
Protection	Cell/Pack Under-voltage Cell/Pack Over-voltage Charge / Discharge Over-current Charge / Discharge Under-temperature Charge / Discharge Over-temperature Mosfet Over-temperature Environment Under-temperature Environment Over-temperature Cell Balancing Fire Aerosol Suppresion System (optional)
Display	LED
Comunication	RS232, RS485, CAN
Storage Environment (50% state of charge)	-20°C ~ 45°C Humidy: 65±20% RH
Environment	Indoor
Installation	Wall mounted /Floor stand
Life Cycle	6000 times @ 80% DOD & 25°C
Cooling	Natural convection
Protection Rating	IP54



Superior
Efficiency



High
Reliability



Scalability
up to 15 units

- Battery monitoring system included
- Scalability up to 15 pcs
- Installation Wall mounted or Floor stand
- Protection IP 54
- Natural cooling, silent operation
- Cell tehnology Lithium - iron phosphate (LifePO4)

Logistics

	Carton Box Size (LxWxH)	633 x 558 x 280 mm
	Pieces in the Carton Box	1
	Net & Gross weight / CTN	Net 48 kg / Gross 51 kg



Certificates

RoHS
2011/65/EU



Safety

CB, IEC62619, UN38.3, MSDS,
CE-EMC, EN61000-6-1/2/3/4;
CE-GPDS, EN62619